



Optional Bucket sizes:	Bucket Width [mm]:	Bucket Capacity [m ³]:
I	275	0.030
II	300	0.036
III	400	0.045
IV	475	0.054
V	750	0.060
VI	575	0.066

	Model Number:	TMB 1800	TMB 2600
A	Min. Recommended Tractor Power [hp/kW]: 3 Point Hitch Category Type Required: Hydraulic System Pressure [MPa/psi]: Hydraulic Flow Rate [l/min / gpm]:	20/15 I 16/2320 28/7	66/49 II 16/2320 28/7
B	Max. Digging Depth [m]: Max. Digging Depth - 2' Flat bottom [m]: Max. Digging Radius [m]:	1.85 1.60 2.75	2.64 2.50 3.93
G	Swing Arc [°]: Stabiliser Spread (Down position, Level ground) [m]: Ground Clearance [mm]:	140 ±1.75 275	140 ±1.75 275
E D A	Loading Height (Bucket at 60°) [m]: Operating Height (Fully raised) [m]: Transport Height [m]:	1.40 2.50 1.73	2.00 3.51 1.96
F	Bucket Rotation [°]: Bucket Capacity (Bucket fitted as std) [m ³]: Bucket Width (Bucket fitted as std) [mm]: 40	160 0.036 (II) 300 (II)	160 0.054 (IV) 450 (IV)
	Nett Weight (Approximate) [kg]:	470	640

*Prices are dependent on exchange rate, please contact Mechanika (Pty) Ltd to confirm.

*Please note that a deposit of 50% is payable to confirm order.

*Delivery time is 8-10 weeks from receipt of order and deposit.

For more information & to order please contact

Schalk Prinsloo at sp@mechanika.co.za | +27 (0) 82 579 1120